



- Notes:**
- 1.Type:Film to Glass
  - 2.Operating Voltage:≤10v
  - 3.Operation Temperature:-20℃~65℃  
Storage Temperature:-30℃~70℃
  - 4.Life Time:1.000.000 times
  - 5.Connect Material:FPC
  - 6.Response Time:≤10ms
  - 7.Linearity:≤1.5%
  - 8.Transmittance:≥75%
  - 9.Surface Hardness≥3H(pencil)
  - 10.Operation force:60g~150g
  - 11.Resistance:X:483Ω-1181Ω Y:151Ω-369Ω

TOLERANCES (UNLESS OTHERWISE STATED)		GreenTouch Technology Co.,Ltd			
DECIMALS	ANGLES ±0.5°	Model No:	GT-4W-215A-1	Size	21.5"
>200MM	±2.00MM	Structure	G+F	Unit	mm
1000<X<2000MM	±1.20MM	Design	李强	Date	2015.7.5
1200<X<1800MM	±0.80MM	Check	李强	Date	2015.7.5
800<X<1200MM	±0.50MM	Release	李强	Date	2015.7.5
400<X<800MM	±0.40MM				
120<X<400MM	±0.30MM				
30<X<120MM	±0.20MM				
<30MM	±0.10MM				
		Ratio	1:1	Scale	1:1
		Page	1/1	Version	A0